



Uniclass
L7626
May 2006

## WebCCTV NVR

### Megapixel IP Camera Video Recorder



Dome Megapixel camera compatible



Standard Megapixel camera compatible

### Features and Benefits

3 year on-site warranty

IP camera recording

Standard IP & megapixel camera compatible

Optional interface for PAL camera

Recording Microsoft Windows Media Player Compatible

Network viewing control

Continuous, motion based and event triggered recording

Instant remote access

Versatile image retrieval and search tools

Digital signature image authentication tools

WebCCTV NVR supports many types of CCTV camera including analogue, IP and megapixel, fixed or pan/tilt/zoom, making it a flexible and future proof solution.

WebCCTV NVR records surveillance video via network directly into native Windows Media Format (WM) without losing the original quality of the image. WM format supports all current video standards including High Definition Television Standards (HDTV standard). Images saved in WM format can be played back via any PC through Windows Media Player, no additional application is required.

Flexible selection of compression techniques enables the users to compress the data into any type of compression. Supporting JPEG, JPEG 2000, MPEG-4, WM and all WM compatible codecs.



### Specifications

Video Cameras	Maximum 10 IP camera
Resolution	1280x960 (HD) 640x240, 320x240
Simultaneous Frame Rate per Camera (max)	15 frames/sec/camera
Compression Techniques	The following compression techniques can be selected on a per camera basis: WM7, WM8, WM9, JPEG,M-JPEG, JPEG 2000 (Wavelet), MPEG4 or any other Windows Media compatible codec
Record Modes	Motion detection schedule based, continuous or event triggered
Alarm Inputs Supported Languages	PIR per camera English, German, French, Italian, Dutch, Spanish, Russian
Logbook Function	Documentation of all error messages, logins and other security relevant parameters
Search Criteria	Date, time, camera number, event, alarm, individual adaptations are available on request
Remote Client Software	Web based, installed upon first remote access
Quality and Bandwidth Control	Adjustable video compression rate, frame rate & resolution rate
Operating System	Windows XP Embedded

### Storage

Storage Capacity	Standard 80GB
Storage Expansion	+ 250 GB
Backup Device	Internal CD-R/RW

### Processor

Processor	Intel Pentium 4
-----------	-----------------

### Interfaces

LAN	LAN/Ethernet Interface (10/100/1000 Mb it), RJ45
Serial	RS-232
Parallel	1x25 pin D-SUB for PC printer
VGA	VGA output connection for VGA/TFT monitor
USB 2	6 USB– 4 powered (3-12V, 1-24V) 2 standard
PS/2	Mouse/keyboard

### Security and Image Authentication

Access Protection	Microsoft Windows certificate based digital signature authentication
Image Authentication	All recordings to hard disk have a digital signature applied at source

### Component Health Service

Both hardware and software watchdog  
SNMP based system health services

### Ambient

Temperature	5-40C (41-104 F)
RH	5-95%, RH non-condensing
Altitude	0-3,048 metres (0-10,000 feet)

### Dimensions

HxWxD	100x338x383 mm
Weight	10kg

### Storage Options

Images can be saved on a secure FTP server, tape  
streamer, DVD, USB/external HDD, flash memory  
sticks etc

Backup capacity can be extended up to 12  
terabyte via external devices

Hard disk capacity can be extended up to 2,4  
terabyte via external devices