



Uniclass
L7626
Sept 2009

Vandal Resistant Camera Housing System

EV Range

ClearView's range of vandal resistant camera housings offer outstanding durability for use in high risk areas vulnerable to physical attack.

The housings will accept all standard CCTV cameras and is suitable for fixed and pan/tilt zoom applications.

Features and Benefits

Concealed "in bracket" cable system

6.0mm glass or high impact polycarbonate window

Rugged heavy gauge aluminium construction

Tamper resistant security fixings

External (Weatherproof to IP66)

CE Approved

12VDC/ 24VAC/ 240VAC heater included



Key features:

Weatherproof to IP66
Stylish design
Stand-off sunshield to protect against solar loading
Maximum tamper resistance
Integral bracket included
Cables are unexposed
Flip top for easy access
Installer friendly
Durable and robust
Energy efficient PTC heater included as standard

Material Specification:

Constructed of extruded and pressure die cast aluminium
Pre treated before polyester powder coated
Window: 6mm quality glass
Fastening and clips: stainless steel

Electrical:

Power consumption at -10°C
Europa 226 8W at 100 VAC
v 10W at 230 VAC
Europa 226L 8.4W at 12VDC
8.6W at 24VAC
Cable entry from wall straight into integral cable managed bracket or through the base of the bracket by drilling a hole through the thin walled recess
Nine Way fused terminal block inside the housing
Fully earth tested and bonded
Insulated camera mounting board

Useful internal dimensions (mm) 225L x 130W x 93H

Weight 3kg

Colour RAL 9002 grey white

Order Codes

E226 and E231 available 12/24 or 240v all have 6.0mm glass window
EV226/ EV231 vandal resistant versions available in 12/24 or 240v with 6.0mm polycarbonate window and tamper screw.